

Auger Force Lux Weighing & Filling Machine

- Model:** Auger Force Lux
- What is it?:** Single head gross weighing and filling machine.
- Special features:** Dedicated drive to buffer hopper product agitation with optional open mouth bag clamp attachment.
- What products can it pack?:** All powders, granules and flakes.
- What industries use this machine?:** Food, non food, pet care, chemical, horticultural and masterbatch.
- What packaging can it fill into?:** Valve sack, open mouth, buckets and drums.
- Min/Max filling weight?:** 2kg - 50kg
- Min/Max valve size:** 120mm - 200mm.
- Typical accuracy:** 0.25% of target weight.
- Typical through put:** Up to 3000kg per hour @ 25kg fill (bulk density 700g / litre).
- Power supply requirements:** 220-240v @ 50Hz 1 phase.
- Compressed air requirements:** 1 cfm @ 3 bar.
- Standard dimensions (HxWxD):** 179cm x 80cm x 170cm.
- Weight:** 180kg.
- Manufacturing material options:** All mild steel, all stainless steel (304/316) or any combination.
- Bag clamp options:** Full size oval clamp, inflatable cuff, gravity flow valve spout, tapered oval bag clamp, twin grip bag clamps, force feed valve spout.


**SIMPLAFILL®
SYSTEMS**



Other available options:

- A range of auger screw pitches and stirrer designs.
- Side entry forklift lifting points.
- A range of auger screw in let designs to suit product.
- Additional control placed in main electrical cabinet for up/down line control.
- Dust extraction cowl assembly.
- ATEX rating.
- Adjustable height sack tipping support (manual and automatic).
- Colour hmi touch screen:
 1. 99 preset target weight memory.
 2. Fast and slow fill value memory.
 3. Product feed rate memory.
 4. Pre set in-flight value.
 5. Fully automatic in-flight correction.
- Adjustable height roller sack support.
- Adjustable height vibrating sack support.
- A range of interchangeable bag clamps.




 Please go to our website to view video of this product.



Hand start fill facility and no bag/no fill sensor for maximum safety.



Features a dedicated variable speed drive for the product agitator.



POWER REQUIREMENTS:
TYPICAL: 220-240 VOLTS 1 PHASE 16 AMP 50HZ
WEIGHT: 180 KG 4 BAR 3 CFM

Drawing available via our website.



Is ATEX required? View our website to read everything your business needs to know! www.atsackfillers.co.uk/ATEX.html



Bespoke applications, design consultancy and turn key solutions.




Please remember: we also supply heat sealers, bag stitchers, conveyors and dust extraction systems.




Contact us for further information, or to discuss your specific requirements.



 **A.T. Sack Fillers**

UK Callers
 **01487 711114**
Web: www.atsackfillers.co.uk

International Callers
 **+44 1487 711114**
Email: enquiries@atsackfillers.co.uk

A.T. Sack Fillers Ltd
12 Biggin Lane,
Ramsey,
Cambs,
PE26 1NB. UK.